

NLS-HR42



Handheld Industrial DPM Barcode Scanner



Features

■ Excellent DPM Decoding Capability

Armed with Newland's latest-generation industrial decoding algorithm, it has strong decoding ability for DPM barcodes such as radium carving and dotting barcodes.

■ New Upgrade of Optical Depth Of Field

It adopts the depth of field design which is more in line with the user's habits.

■ Easy to Configure and Update

By configuring the software NSet, the scanner's functions can be diversified configuration.

■ High-Resolution Image Sensor

Using 1280×960 megapixels image sensor, the scanner can decode higher precision barcodes.

■ High Protection Industrial Structure Design

The NLS-HR42 adopts a more suitable sound cavity design, high elastic trigger design, which is more ergonomic and has better pull feedback. It is built into an IP42-sealed, which can withstand repeated falls from 1.8 meters to the ground, with excellent reliability and stability.

Application Scenarios

Electronic production traceability management, metal manufacturing traceability management, auto parts quality traceability management.

Handheld Industrial DPM Barcode Scanner

Performance	Image Sensor	1280×960 CMOS	
	Illumination	White LED;	
	Aiming	650nm laser diode	
	Symbolologies	2D	QR Code, Micro QR Code, PDF 417, Data Matrix.
		1D	EAN-8, EAN-13, UPC-E, UPC-A, Code 128, UCC/EAN128, Interleaved 2 of 5, ITF-14, ITF-6, Matrix 2 of 5, CodaBar, Code 39, Code 93, ISSN, ISBN, Industrial 25, Standard 25, Plessey, Code 11, MSI Plessey, AIM 128, ISBT 128, COOP 25, Deutsche14, Deutsche12.
	Resolution*	≥3mil	
	Typical Depth of Field*	EAN-13(13mil)	25mm-160mm
		Code 39(5mil)	40mm-100mm
		Code 39(20mil)	35mm-210mm
		Data Matrix(10mil)	0mm-125mm
		QR Code(20mil)	20mm-180mm
	Motion Tolerance*	2m/s	
	Scan Angle**	Roll: 360°, Pitch: ±50°, Skew: ±50°	
Field of View	Horizontal 41°, Vertical 31°		
Min. Symbol Contrast*	25%		
Mechanical/	Interfaces	RS-232, USB	
Electrical	Dimensions	74(W) × 115(D) × 161(H) mm (max.)	
	Weight	173g	
	Notification	Beep, LED indicator, Vibration	
	Rated Power Consumption	2220.8mW (typical)	
	Operating Voltage	5VDC±5%	
	Current@5VDC	Operating	401.5mA (max.)
		Idle	109mA
Environmental	Operating Temperature	-20°C to 50°C (-4°F to 122°F)	
	Storage Temperature	-40°C to 70°C (-40°F to 158°F)	
	Humidity	5%~95% (non-condensing)	
	Ambient Light	0~100,000lux (natural light)	
	ESD	±8 KV (direct discharge); ±16 KV (air discharge)	
	Drop	1.8m	
	Sealing	IP42	
Certifications	CE EMC Class B, FCC Part15 Class B, RoHS, IEC62471, EN 60825-1:2014		

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp; 2D QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: 1.0

Newland Headquarter

Add: NO.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350015, China
Tel: +86 591 8397 9500
Email: info@nlscan.com
Web: www.newlandaidc.com

Newland APAC

Taiwan Tel: +886 2 7731 5388
Taiwan Email: info@newland-id.com.tw
Web: www.newland-id.com.tw
Japan Tel: +886 2 7731 5388 ext. 71
Korea Tel: +82 10 8990 4838
India Tel: +91 120 7964266
Japan/Korea/India Email: info@nlscan.com
Web: www.newlandaidc.com

Newland NALA

North America Tel: +1 510 490 3888
North America Email: info@nlscan.com
Latin America Tel: +1 239 598 0068
Latin America Email: info@newlandla.com
Web: www.newlandamerica.com

Newland EMEA

Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com
Web: www.newland-id.com